



WYTWÓRNIA  
LAKIERÓW

**TUKAN**

St. Chmiełek & St. Chmiełek



**Intended use: TUKMAL-L is a preparation for maintenance and renovation of natural and artificial stone (terrazzo) and PVC.**

Application of this preparation results in a long-lasting effect – “casting effect”, e.g. PVC floors, as well as revival and enhancement of the stone structure, e.g. terrazzo. The surfaces are not polished after casting.

TUKMAL-L is used for maintenance and renovation of painted wooden floors and stone floors, as well as tombstones.

**Characteristics: TUKMAL-L** is an ecological product.

It is a high wax preparation based on polymer resin. It is water-thinnable. It does not contain any organic solvents harmful to health, non-combustible. It contains very pure synthetic wax with a high softening point. The use of such wax guarantees no darkening with time and high durability. The preparation shows very good adhesion to a clean substrate. The coating clogs pores of the substrate and makes it harder for them to get dirty. Gloss remains on PVC and ground terrazzo for a long time. It also protects against erosion.

**Instructions for use:** Apply an even layer on a clean surface with brush or tampon. Apply two layers for a good effect.

Gloss is obtained without polishing.

**Spreading rate:** 10–30m<sup>2</sup> with 1 dcm<sup>3</sup> depending on the substrate.

**Notes: Fire and health advice**

1. Mix before use.
2. Use and store at temperatures above 5°C.
3. Frozen preparation is not suitable for use.
4. Preparation is non-combustible.
5. Even when handling ecologically safe products, the general rules on health and safety must be observed.

TUKMAL-L

**P.P.U.H. TOUCAN**

Łany 6 Street, 32-700 Bochnia, phone: (14) 611 25 78 ex. 21-28,  
e-mail: [tukan@ekolakieri.pl](mailto:tukan@ekolakieri.pl), [www.ekolakieri.pl](http://www.ekolakieri.pl)